

條碼掃描器

SW111

無線體驗 · 無限效能



掃碼支援
1D/2D



藍牙
BT5.0



密封等級
IP40



全域式快門
1280 x 800 像素



重量
170g



倉儲



製造



零售



物流



SW111

規格表

更新時間: 2023.07.06

外觀特色

尺寸	197mm* 71.9mm* 68mm
重量	170g
顏色	黑色
線材長度	1.8m

光學性能

光源及照明	白色照明 LED · 紅色瞄準 LED
影像感測	1280 x 800 像素 · 全域式快門
印刷對比 (PCS)	最高 0.20 (最低 20% 的印刷對比)
掃描速度	60 fps
位移容忍度	<ul style="list-style-type: none">最高: 600 cm/s (236 in/s)典型: 400 cm/s (157 in/s)
掃描角度	<ul style="list-style-type: none">前後: ±60°左右: 60°旋轉: 360°
掃描視野	<ul style="list-style-type: none">水平: 48°垂直: 31°

解碼能力

掃碼引擎	1D/2D
------	-------

支援條碼類型

- **Barcode (1D):**
Codabar, Code 11, Code 128, Code 2 of 5, Code 39, Code 93 and 93i, EAN/JAN13, EAN/JAN8, IATA code 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, GS1 Databar, UPC-A, UPC E, UPCA/EAN-13 with Extended coupon Code, Coupon GS1 Code 32 (PARAF), EANUCC Emulation
- **Postal code:**
Australian Post, British Post, Canadian Post, China Post, Japanese Post, Korea Post, Netherlands Post, Planet Code, Postnet
- **2D Stacked:**
Codablock A, Codablock F, PDF417, MicroPDF417
- **2D Matrix:**
Aztec Code, Data Matrix, MaxiCode, QR Code, Chinese Sensible (Han Xin) Code

分辨率	2.5mils (Code 39), 5mils (Data Matrix), 5mil (QR), 4mils (PDF417)
-----	---

- | | |
|------|---|
| 掃碼距離 | <ul style="list-style-type: none">• 最近: 4cm / 1.57in (Code 39, PSC 0.9, 10mil)• 最遠: 51.7cm / 20.3in (Code 39, PSC 0.9, 10mil)• UPC-A 掃描景深:
44 ~ 573mm / 1.73 ~ 22.5 in (13mil)• Code 39 掃描景深:
70 ~ 301 mm / 2.76 ~ 11.85 in (5 mil)
40 ~ 517 mm / 1.57 ~ 20.3 in (10 mil)
44 ~ 800 mm / 1.73 ~ 31.5 in (20 mil)• Code 128 掃描景深:
42 ~ 650 mm / 1.65 ~ 25.6 in (15 mil)• Data Matrix 掃描景深:
72 ~ 297 mm / 2.84 ~ 11.7 in (10 mil)• PDF417 掃描景深:
84 ~ 244 mm / 3.3 ~ 9.6 in (6.7 mil)• QR Code 掃描景深:
39 ~ 414 mm / 1.54 ~ 16.3 in (15 mil) |
|------|---|

傳輸介面

通訊接口	USB HID, USB COM, SPP, Master
無線傳輸	藍牙 BT5.0 · 傳輸範圍約 3~5m

電力

電壓需求	DC 5V ± 5%
電流消耗	低於 200mA (操作中) · 低於 25mA (待機)
電池	<ul style="list-style-type: none">• 2040mAh 鋰電池 (定制 18500 帶保護電路)• 充電時間: 4.5 小時

使用環境

操作溫度	-10~40 °C (14~40 F)
儲存溫度	-40C~60C (-40 ~76 F)
環境溼度	5%~95% RH
抗環境光干擾強度	0 到 100,000 lux
密封等級	IP40
落摔高度	1m

合規性

安規認證	CE/ FCC/ VCCI/ BSMI/ NCC/ TELEC
------	---------------------------------

系統支援

系統支援	Windows
------	---------

配件

配件	<ul style="list-style-type: none">• 磁吸式充電線• 免持支架 (選配)• USB dongle (選配)
----	--