

Mobile Computer

TC605

Brand New 5G / Wi-Fi 6E Mobile Computer



Qualcomm®

QCM4490 2.4GHz Octa Core



OS

Android 13

(upgradeable to Android 18)



Drop Test 1.8m



Sealing Standard

IP65 & IP68



Memory 6GB/128GB

919 82.0 Scan Engine

Long Range / Short Range



Weight 280g

4

Battery

5000mAh



Warehouse



Logistics



Retai



Manufacturing



Field Service



TC605 Specification

Update Date: 2024.01.04

·	
Physical Characteristics	
Dimensions	167.7 x 78.9 x 15.8 mm
Weight	280g (with standard battery)
Display and Panel	• 6", 18:9 IPS Full-HD (1080 x 2160)
	Gorilla® Glass 7 600 nits
Expansion Slots	 Micro SD card slot x 1 (with SDHC compliance and software image upgrade features) Nano SIM slot x 2 USB 3.1 (Type-C) support USB OTG Compliance with PD3.0 / QC3.0 / QC4.0 8 POGO Pin for extension + 2 POGO Pin for charging
Keys and Buttons	 Virtual key x 3 Scan key x 2, Volume key x 2, Power key, Function key (programmable)
Indicators	Support RGB LED (Complied with SW)
Audio and Voice	 Speaker x 1 (95dB @ 10cm) Receiver x 1, Dual noise-cancelling microphones x 1 Support Type-C headsets Support Smart PA
Performance (Characteristics
Operating System	Android 13 with GMS (upgradeable to Android 18)
CPU	Qualcomm [®] QCM4490, 2.4GHz Octa Core
Memory	 RAM 6 GB + ROM 128 GB RAM 8 GB + ROM 128 GB (Optional)
GMS Certification	GMS certified
Android Enterprise	AER certified

User Environment	
Operating Temp.	-20~50℃
Storage Temp.	-40~60℃
Charging Temp.	0~45℃
Humidity	5%~95% (non-condensing)
Sealing	IP65 & IP68 Standard
Drop Spec.	1.8 meter drop (2.1 meter drop with protective boot)
Tumble Spec.	0.5m tumbles for 500 cycles and 1000 drops
ESD	±8KV direct discharge, ±15KV air discharge
Network Conr	nection
Wireless PAN	Bluetooth 5.2
Wireless LAN	 802.11a/b/g/n/d/h/i/k/r/ac/ax/v/mc 2.4GHz, 5GHz, 6GHz Compliant with WEP, WPA and IEEE 802.11i WPA2, WPA3 Fast Roaming
Wireless WAN	 5G: FDD bands: n1, n2, n3, n5, n7, n8, n12, n20, n25, n28, n66 TDD bands: n38, n40, n41, n48, n77, n78, n79 4G: FDD bands: B1, B2(25), B3, B4(66), B5, B7, B8, B12, B17, B18, B19, B20, B26, B28 TDD bands: B38, B39, B40, B41, B42, B43, B48 3G: B1, B2, B4, B5, B6, B8, B19 2G: 850, 900, 1800, 1900
GPS	GPS, GLONASS, Beidou, Galileo, QZSS, SBAS (5G SKU)
Data Capture	
Scanner	Support 1D/2DLong range / Short range (Selectable)
Scan angle	0° / 60° (Selectable)
Camera	Front camera: 8M pixel CMOS color camera Rear camera: 16M pixels CMOS color camera with auto focus LED flashlight

NFC · ISO14443-4 (Type A, Type B), ISO15693 · MIFARE, FeliCa (ISO/IEC18092) Software Software iMozen SEK[™] (Software Extension Kit): EMM / MDM · Software updates RDM · Other customized solution OCR Sensor Sensor Gyroscope, Light sensor, e-Compress, Proximity sensor, Accelerator sensor Power Battery · Replaceable battery: 5000mAh · Support battery swap Power Adaptor · 100~240Vac, 50/60Hz Input 9V/2A 18W output (Support QC3.0) **Regulatory Compliance** Certifications · CE, CB, FCC, NCC, BSMI(Wi-Fi), UKCA, TELEC, VCCI, JATE, BQB, RCM · RoHS, REACH and WEEE Accessories Accessories Adapter · USB Cable (Type-C) · Screen Protector (Optional) Rugged Protective Boots (Optional) Hand Strap (Optional)

- Shoulder Strap (Optional)
- Spare Battery (Optional)
- Soft Holster (Optional)
- Pistol Grip (Optional)
- Multi-Slot Cradle (Optional)